



## Two of our Most Spectacular Fountains Now Available in 1/2 HP



### **THE 1/2 HP ATRIARCH**

The Atriarch's sophisticated design, paired with the serene flow of its cascading water, creates a dynamic water display suitable for both home and business settings. It is crafted using a durable brass nozzle featuring one central jet and eight surrounding jets.



### **THE 1/2 HP AMHERST**

A classic. This stately pattern provides a very distinct separation of all three tiers capped by an impressive center water height. The Amherst is stunning in both sight and sound, and the large flow rate creates a pleasing ripple effect across the water's surface.



## The Atriarch Fountain 1/2 hp




- 1/2-hp, 115-volt, oil-free motor. Also available in 230-volt model.
- 45 gallons-per-minute flow rate.
- Center Stream: 20 feet high.
- Side jets angled spray pattern is 35 feet in diameter.
- Electric power cord provided is 70 feet in length, 12-gauge submersible. Can be ordered in greater lengths.
- Light kits can be added now or later.
- Approved for use in saltwater.
- Two 20-pound weights or concrete blocks required for anchoring (not included).
- Two nylon ropes required for anchoring (not included).
- Designed for 24-hour-per-day operation.
- No maintenance is required.
- 36-inch minimum pond depth required.
- 5-year motor warranty.
- ARL tested and approved to be in compliance with the applicable requirements of UL and the National Electric Code as complete packages.

## The Amherst Fountain 1/2 hp



- 1/2-hp, 115-volt, oil-free motor. Also available in 230-volt model.
- 45 gallons-per-minute flow rate.
- Center Stream: 15 feet high.
- Side jets angled spray pattern is 30 feet in diameter.
- Electric power cord provided is 70 feet in length, 12-gauge submersible. Can be ordered in greater lengths.
- Light kits can be added now or later.
- Approved for use in saltwater.
- Two 20-pound weights or concrete blocks required for anchoring (not included).
- Two nylon ropes required for anchoring (not included).
- Designed for 24-hour-per-day operation.
- No maintenance is required.
- 36-inch minimum pond depth required.
- 5-year motor warranty.
- ARL tested and approved to be in compliance with the applicable requirements of UL and the National Electric Code as complete packages.



Lighting Packages Available

	1/2 HP 115V Single Phase	1/2 HP 230V Single Phase
Hz	60	60
KWs	.37	.37
AMPS	10	5
MIN ANCHOR WT (ea)	20 lbs	20 lbs
<b>MAXIMUM CABLE LENGTH IN FEET FROM MOTOR TO MAIN BREAKER</b>		
12 AWG	160'	650'
10 AWG	250'	1020'
8 AWG	390'	1610'
CABLE SUPPLIED	70' 12 AWG	70' 12 AWG

## The Scott Aerator Awesome Warranty

All standard Scott Aerator products are unconditionally warranted for five years against motor defects in materials or workmanship, under normal operating conditions. All other product components are warranted for one year from date of purchase. Scott Aerator will repair or replace failed parts under warranty when the defective unit is returned to the factory, shipping prepaid, and factory inspection establishes that the part was defective. The unit must be returned to the factory prior to shipment of replacement parts. All parts replaced under this warranty will be returned with shipping prepaid. Scott Aerator will not be liable for consequential damage nor for any costs associated with removal or attempts to repair components in the field.



13245 Barry Street, Holland, MI 49424  
 scottaerator.com information@scottaerator.com  
 800-WATER-45 (800-928-3745) (616) 392-8882

